

03 - 02 - 00

PATENT

A

03/01/00
jc714 U.S. PTO

Attorney's Docket No. 99-003

jc678 U.S. PTO
09/516090
03/01/00

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Box Patent Application
Assistant Commissioner for Patents
Washington, D. C. 20231

NEW APPLICATION TRANSMITTAL

Transmitted herewith for filing is the patent application of:

Inventor(s): Walter Wesley Howe

For: METHOD AND SYSTEM FOR COMMUNICATING DATA FROM
WIRELINE TERMINALS TO MOBILE TERMINALS

Certification Under 37 CFR 1.10

I hereby certify that this New Application Transmittal and the documents referred to as enclosed therein are being deposited with the United States Postal Service on this date 03/01/00 in an envelope as "Express Mail Post Office to Addressee" mailing label EJ871293729US addressed to the: Assistant Commissioner for Patents, Washington, D.C. 20231.

Mary E. Anza

(typed or printed name of person mailing paper)

Mary E. Anza
(Signature of person mailing paper)


Attorney's Docket No. 99-003

Enclosed are:

[16] pages of specification and cover sheet
 [7] pages of claims
 [1] page of abstract
 [9] sheets of formal drawings.
 [2] pages of declaration and power of attorney.
 [2] pages of assignment and assignment recordation form
 [2] pages of information disclosure statement
 [1] page of form 1449
 [2] references
 [1] return postcard

CLAIMS AS FILED			
	NUMBER FILED	NUMBER EXTRA	BASIC FEE \$690.00
TOTAL CLAIMS	30 - 20	10 x	\$18.00
INDEPENDENT CLAIMS	7 - 3	4 x	\$78.00
MULTIPLE DEPENDENT CLAIMS(S)		0 x	\$260.00
TOTAL FILING FEE			\$1182.00

- [x] Please charge my Deposit Account No. 07-2339 in the amount of \$1182.00. **This transmittal letter is submitted in duplicate.**
- [x] The Commissioner is hereby authorized to charge any additional fees under 37 CFR 1.16 and 1.17 which may be required by the papers submitted herewith or credit any overpayment to Account No. 07-2339.
This transmittal letter is submitted in duplicate.



W. Eric Webostad
Registration No. 35,406
Attorney for Applicant(s)

GTE Service Corporation
600 Hidden Ridge, HQE03G13
Irving, TX 75038
Phone: (781) 466-4013
Fax: (781) 466-4021

EXPRESS MAIL NO. EJ871293729US

PATENT
GTE DOCKET NO. 99-003

UNITED STATES PATENT APPLICATION

OF

Walter Wesley HOWE

FOR

METHOD AND SYSTEM FOR COMMUNICATING DATA
FROM WIRELINE TERMINALS TO MOBILE TERMINALS

[illegible]

5

Field of the Invention

10

15

20

25

30

One problem with the present telecommunication networks is that two connections must be established when a call is placed to a wireless DN whose associated wireless device is outside

of its home area. In such instances, the telecommunications network must establish a first connection to the home wireless switch associated with the wireless DN. The home wireless switch then must establish a second connection to a visited wireless switch serving the wireless DN.

5 As an illustration, consider data communication applications in the trucking and postal industries. These industries often use complex data communication networks for controlling and monitoring from fixed locations the activities of field personnel who are mobile and are geographically dispersed over a wide area. These data communication networks typically use conventional telecommunications networks for establishing communication between wireline
10 data processing devices, such as desk top computers located in centralized offices, and wireless data processing devices, such as mobile terminals used by field personnel.

Figure 1 shows a block diagram of one such conventional telecommunications network 100. Telecommunications network 100 comprises a wireline switch 110, a home wireless switch 120, a home location register 130, a signal transfer point (STP) 135, a visited
15 location register 140, a visited wireless switch 150, a wireline terminal 155, such as a desktop personal computer, antenna 170, wireless modems 175₁-175_K, and mobile terminals 178₁-178_K. Wireline terminal 155 establishes communication with mobile terminals 178₁-178_K via wireless modems 175₁-175_K, respectively.

To establish communication with one of mobile terminals 178₁-178_K, for example mobile
20 terminal 178₁, wireline terminal 155 executes a dialup program, such as the Microsoft Dialer software developed by Microsoft. The dialup program initiates a call request 180a by dialing the wireless DN associated with wireless modem 175₁. When wireline switch 110 receives call request 180a, wireline switch 110 establishes a first connection 180b via a Public Switched Telephone Network (PSTN) 160 to home wireless switch 120, the home switch associated with
25 the dialed wireless DN.

Home wireless switch 120 sends an "Interim Standard 41" (IS-41) RouteRequest message 180c to its associated home location register 130, requesting the current location of

wireless modem 175₁. The ANSI-41 standard is described in "Radio Telecommunications Intersystem Operations," ANSI/TIA/EIA/41-D-1997, which is incorporated herein by reference. The IS-41 standard describes the communication protocol between home wireless switch 120, home location register 130, visited location register 140, and visited wireless switch 150 in telecommunications network 100.

If wireless modem 175₁ is outside of its home area as shown in Figure 1, home location register 130 then identifies the visited location register with which wireless modem 175₁ last registered, for example visited location register 140, and sends an IS-41 RouteRequest message 180d via STP 135 to visited location register 140.

Visited location register 140 forwards the RouteRequest message 180d to its associated visited wireless switch 150, requesting a route to wireless modem 175₁. Visited wireless switch 150 computes a temporary local directory number (TLDN), which is used to establish incoming calls to wireless modem 175₁ when wireless modem 175₁ is served by visited wireless switch 150. Visited wireless switch 150 then returns the TLDN to visited location register 140 in an IS-41 message 180e. Visited location register 150 then sends via STP 135 to home location register 130 an IS-41 RouteRequest response message 180f that includes the TLDN.

Home location register 130 forwards the RouteRequest response message 180f to home wireless switch 120. Based on the TLDN in the RouteRequest response message 180f received from home location register 130, home wireless switch 130 then establishes a second connection 180g to visited wireless switch 150. Visited wireless switch 150 then sends a ring signal to wireless modem 175₁. When wireless modem 175₁ receives the ring signal, wireless modem 175₁ notifies a dialup program running on mobile terminal 178₁, such as the Microsoft Dialer software developed by Microsoft and, waits for a response. When the dialup program responds, wireless modem 175₁ sends an answer signal via visited wireless switch 150 to wireline terminal 155, thus establishing a call between mobile terminal 178₁ and wireline terminal 155. Accordingly, telecommunications network 100 must establish two separate connections 180b and 180g to establish communication between wireline terminal 155 and

mobile terminal 178₁ when mobile terminal 178₁ resides outside of its home area.

SUMMARY OF THE INVENTION

It is therefore desirable to have a method and system for reducing the number of
5 connections that must be established in a telecommunications network to communicate data from
a wireline terminal to one or more mobile terminals that are located outside of their respective
home areas.

Methods and systems consistent with the present invention communicate data from a
wireline terminal to a mobile terminal in a telecommunications network, which includes a home
10 node associated with the mobile terminal and one or more visited nodes. The home node serves
the mobile terminal when the mobile terminal is in a geographical area served by the home node.
However, when the mobile terminal is outside of the geographical area served by home node, one
of the visited nodes serves the mobile terminal.

To establish communication with the mobile terminal, the wireline terminal sends data to
15 a server in the telecommunications network. The server identifies a mobile identification number
associated with the mobile terminal, and based on the identified mobile identification number,
the server determines a route that excludes the home node when the mobile terminal is out of the
geographical area served by the home node. The server then establishes via the determined route
a connection to the mobile terminal and sends on that connection the data received from the
20 wireline terminal to the mobile terminal.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing summary and the following description of the invention should not restrict
the scope of the claimed invention. Both provide examples and explanations to enable others to
25 practice the invention. The accompanying drawings, which form part of the description of the
invention, show several embodiments of the invention, and together with the description, explain
the principles of the invention.

In the Figures:

Figure 1 is a block diagram of a conventional telecommunications network;

Figure 2 is a block diagram of a telecommunications network, in accordance with methods and systems consistent with the present invention;

5 Figure 3 is a block diagram of a server node in a telecommunications network, in accordance with methods and systems consistent with the present invention;

Figure 4 is a block diagram of a mobile identification table in a server node, in accordance with methods and systems consistent with the present invention where each mobile terminal is associated with a unique mobile terminal identifier;

10 Figure 5 is a block diagram of a home location register identification table in a server node, in accordance with methods and systems consistent with the present invention;

Figure 6 is a flow chart of the steps performed by a connection module in a server node, in accordance with methods and systems consistent with the present invention;

15 Figure 7 illustrates a packet format for communication between a wireline terminal and a server node, in accordance with methods and systems consistent with the present invention, where each mobile terminal is associated with a unique mobile terminal identifier;

20 Figure 8 is a block diagram of a mobile identification table in a server node, in accordance with methods and systems consistent with the present invention, where the server node is assigned a plurality of Internet Protocol (IP) addresses which the server node associates with a plurality of mobile terminals; and

Figure 9 illustrates a packet format for communication between a wireline terminal and a server node, in accordance with methods and systems consistent with the present invention, where each mobile terminals is associated with a unique IP address.

25

DETAILED DESCRIPTION

The following description of embodiments of this invention refers to the accompanying drawings. Where appropriate, the same reference numbers in different drawings refer to the

same or similar elements.

A telecommunications network in accordance with methods and systems consistent with the present invention comprises a wireline terminal, a plurality of mobile terminals, a home switch associated with one or more of the mobile terminals, one or more visited switches, and a server. To establish communication with a mobile terminal, the wireline terminal sends via a packet network data packets to the server. Based on information in the data packets, the server identifies a mobile identification number associated with the mobile terminal. In one embodiment, the information in the data packets may include a mobile terminal identifier associated with one of the mobile terminals. In another embodiment, the information in the data packets may include one of a plurality of IP addresses assigned to the server.

The server then determines a route depending on the geographical location of the mobile terminal. If the mobile terminal is outside of a geographical area served by the home switch, the determined route excludes the home switch. However, if the mobile terminal is within the geographical area served by the home switch, however, the determined route includes the home switch. The server then establishes via the determined route a connection to the mobile terminal and sends the data packets on that connection to the mobile terminal.

Figure 2 is a block diagram of a telecommunications network 200 in accordance with methods and systems consistent with the invention. As shown, telecommunications network 200 comprises a server node 210, packet network 220, signal transfer points (STPs) 135 and 235, wireline switch 110, home wireless switch 120, home location register 130, visited location register 140, visited wireless switch 150, antenna 170, wireless modems 175₁-175_K, and mobile terminals 178₁-178_K.

Server node 210 interfaces wireline switch 110, STP 235, and packet network 220. As described below, server node 210 receives via packet network 220 data packets destined for mobile terminals 178₁-178_K and sends the data packets to mobile terminals 178₁-178_K by establishing in telecommunications network 200 a single connection to each of wireless modems 175₁-175_K associated with mobile terminals 178₁-178_K regardless of whether wireless modems

175₁-175_k reside within or outside of their respective home areas.

Packet network 220 may include an Internet Protocol (IP) network capable of transporting packets from wireline terminal 155 to server node 210.

Home location register 130 interfaces via STP 235 with server 210 and via STP 135 with
5 visited location register 140. Home location register 130 stores information about wireless subscribers in telecommunications network 200, such as the current location of wireless modems 175₁-175_k, billing information for wireless modems 175₁-175_k, and the services wireless modems 175₁-175_k are authorized to use.

Visited location register 140 stores information about the current location of wireless
10 modems 175₁-175_k when wireless modems 175₁-175_k reside outside of their respective home areas. For example, wireless modem 175₁ resides within its home area when wireless modem 175₁ directly communicates with home wireless switch 120. However, wireless modem 175₁ resides outside of its home area when wireless modem 175₁ cannot directly communicate with home wireless switch 120 and instead communicates with, for example,
15 visited wireless switch 150.

STPs 135 and 235 route signaling messages such as, IS-41, Advanced Intelligent Network (AIN), and SS7 messages in telecommunications network 200. Each STP 135 and 235 may be an adjunct to a wireline or a wireless switch in telecommunications network 200.

Figure 3 is a block diagram of server node 210 in accordance with methods and systems
20 consistent with the invention. Server node 210 may be a SUN Microsystems, Inc. server configured with the SOLARIS™ operating system. As shown, server node 210 comprises a processor 300, which connects via bus 310 to a memory 320, secondary storage 330, peripheral module 340, packet network interface 350, signaling module 360, input terminal 370, and an output terminal 375.

25 Memory 320 includes a connection module 380, an operating system 382, a mobile identification table 384, and an HLR identification table 386. Connection module 380 includes software and information for establishing, maintaining, terminating, and managing

communication between wireline terminal 155 and mobile terminals 178_I-178_K. Mobile identification table 384 includes information for identifying mobile identification numbers (MINs) associated with wireless modems 175_I-175_K. HLR identification table 386 includes information for identifying home location registers associated with wireless modems 175_I-175_K.

5 Secondary storage 330 includes a computer readable medium such as a disk drive and a tape drive. From the tape drive, software and data may be loaded onto the disk drive, which can then be copied into memory 320. Similarly, software and data in memory 320 may be copied onto the disk drive, which can then be loaded onto the tape drive.

10 Peripheral module 340 includes software and data for interfacing a bank of modems (not shown) through which connection module 380 establishes calls to mobile terminals 178_I-178_K. The bank of modems interface with wireline switch 110 and wireless switch 120 and may include, for example, a plurality of Total Control™ Multiservice Access Platform modems manufactured by 3Com Corporation. Peripheral module 340 may establish the calls using any known dialup protocol such as, the Point-To-Point protocol.

15 Packet network interface 350 includes software and data for interfacing packet network 220. For example, packet network interface 350 transmits and receives IP packets via packet network 220. Packet network interface 350 segments data received from connection module 380 into IP packets, and using a transport protocol such as, the Transmission Control Protocol over IP (TCP/IP) protocol, transmits the packets via packet network 220 to wireline
20 terminal 155. Likewise, packet network interface 350 receives IP packets from wireline terminal 155 via packet network 220 and reassembles the packets into an internal format for processing by connection module 380.

25 Signaling interface module 360 transmits and receives via STP 225 signaling information, such as IS-41 messages. For example, signaling interface module 360 converts signaling information generated by connection module 380 into IS-41 messages and transmits the messages to STP 235. Likewise, signaling interface module 350 receives IS-41 messages from STP 235 and converts the messages into an internal format for processing by connection

module 380.

Input terminal 370 may include an input device such as, a keyboard, and output terminal 375 may include a display device.

In one embodiment, mobile identification table 384 in server node 210 is configured to
5 associate mobile terminal identifier (ID) information in the data packets received from wireline terminal 155 to a mobile identification number associated with one of wireless modems 175₁-175_K. In this embodiment, to establish communication with one of mobile terminals 178₁-178_K, for example mobile terminal 178₁, wireline terminal 155 segments data into one or more data packets 230a each of which includes mobile terminal ID information associated with mobile
10 terminal 178₁. Wireline terminal 155 then sends the data packets 230a via packet network 220 to server node 210. Based on the mobile terminal ID information in the data packets 230a, server node 210 identifies a mobile identification number associated with wireless modem 175₁. As shown below, based on the identified mobile identification number, server node 210 then establishes a connection to mobile terminal 178₁ via wireless modem 175₁.

15 Figure 4 is a block diagram of mobile identification table 384 in server node 210, in accordance with an embodiment where mobile identification table 384 is configured to associate mobile terminal ID information to mobile identification numbers associated with wireless modems 175₁-175_K. As shown, mobile identification table 384 includes entries 400₁-400_N, where N is an integer. Each entry includes a mobile terminal ID 410 and a mobile identification
20 number 420. Each mobile identification number 420 identifies one of wireless modems 175₁-175_K.

Figure 5 is a block diagram of HLR identification table 386 in server node 210, in accordance with methods and systems consistent with the invention. HLR identification table 386 includes entries 500₁-500_M, where M is an integer. Each entry includes a range
25 begin 510, a range end 520, and a point code 530. Range begin 510 includes a 10 digit string, such as a mobile identification number, which identifies a beginning of a range of mobile identification numbers. Range end 520 also includes a 10 digit string, such as a mobile

identification number, which identifies an end of the range of mobile identification numbers. Point code 530 includes a numeric string that identifies in telecommunications network 200 a home location register associated with mobile identification numbers that are in the range of mobile identification numbers identified by range begin 510 and range end 520.

5 Figure 6 is a flow chart of the steps performed by connection module 380 in server node 210, in accordance with methods and systems consistent with the invention. Connection module 380 receives one or more data packets 230a from wireline terminal 155 (step 600). For example, to communicate data with one of mobile terminals 178₁-178_K, for example mobile terminal 178₁, wireline terminal 155 establishes a TCP/IP connection to server node 210 via
10 packet network 220. Wireline terminal 155 then segments the data into one or more data packets 230a each of which includes a mobile terminal ID associated with mobile terminal 178₁. Wireline terminal 155 then sends the data packets 230a over the TCP/IP connection to server node 210.

15 Figure 7 illustrates format of each data packet 230a, in accordance with an embodiment of the invention. In the embodiment shown, each data packet 230a may be in the form of an IP packet, which includes a header field 710 and a payload field 720. Payload field 720 may include a data portion 722 and a mobile terminal ID portion 724. Data portion 722 may include information in any format such as, text, video, and audio. Mobile terminal ID portion 724 may identify one of mobile terminals 178₁-178_K, for example mobile terminal 178₁.

20 When connection module 380 receives the data packets 230a from wireline terminal 155, connection module 380 determines whether a connection already exists from server node 210 to mobile terminal 178₁ (step 610). If connection module 380 determines that a connection exists, connection module 380 sends data portion 722 of each of the data packets 230a to mobile terminal 178₁ via the existing connection (step 620).

25 However, if connection module 380 determines that a connection does not exist from server node 210 to mobile terminal 178₁, connection module 380 determines a mobile identification number associated with wireless modem 175₁ (step 630). For example, using

mobile terminal id 724 as an index into mobile identification table 384, connection module 380 identifies an entry that includes the mobile identification number associated with wireless modem 175₁.

Based on the determined mobile identification number, connection module 380 then
5 identifies a home location register associated with wireless modem 175₁ (step 640). For example, using the determined mobile identification number as an index into HLR identification table 386, connection module 380 identifies an entry whose range begin 510 and range end 520 define a set of mobile identification numbers that includes the determined mobile identification number. Connection module 380 then uses point code 530 in that entry to identify an associated
10 home location register, for example, home location register 130.

Connection module 380 sends an IS-41 LocationRequest message 230b via STP 235 to the identified home location register 130, requesting a route for establishing a call to the identified mobile identification number (step 650). In response to the IS-41 LocationRequest message 230b, connection module 380 may receive from home location register 130 a IS-41
15 LocationRequest response message 230c (step 660).

Connection module 380 then determines whether the IS-41 LocationRequest response message 230c includes a temporary local directory number (TLDN) (step 670). If the IS-41 LocationRequest response message 230c does not include a TLDN and instead includes the mobile identification number associated with wireless modem 175₁, connection module 380
20 determines that wireless modem 175₁ resides within its home area.

Using the mobile identification number associated with wireless modem 175₁, connection module 380 then establishes a call to wireless modem 175₁ via a route that includes home wireless switch 120 as follows (step 680): Connection module 380 seizes via peripheral module 340 a modem from the bank of modems interfacing home wireless switch 120.
25 Connection module 380 then initiates a call to wireless modem 175₁ via the modem and home wireless switch 120 using the mobile identification number associated with wireless modem 175₁. Connection module 380 may initiate and establish the call using a dialup protocol,

such as the Point-To-Point protocol. For example, connection module 380 may invoke a dialup program, such as the Microsoft Dialer software developed by Microsoft, to establish the call. When the call is established, connection module 380 then sends the data portion 722 of each of the data packets 230a via the established call to mobile terminal 178₁.

- 5 However, if the IS-41 LocationRequest response message 230c includes a TLDN associated with wireless modem 175₁, connection module 380 determines that wireless modem 175₁ resides outside of its home area as shown in Figure 2. Server node 210 receives the TLDN associated with wireless modem 175₁ as follows: In response to the IS-41 LocationRequest message 230b received from server node 210, home location register 130
- 10 identifies a visited location register with which wireless modem 175₁ last registered, for example visited location register 140, and sends an IS-41 RouteRequest message 180d via STP 135 to the identified visited location register 140. Visited location register 140 then forwards the IS-41 RouteRequest message 180d to its associated visited wireless switch 150, requesting a route to wireless modem 175₁.
- 15 Visited wireless switch 150 computes a TLDN for establishing incoming calls to wireless modem 175₁ when wireless modem 175₁ is served by visited wireless switch 150. Visited wireless switch 150 then returns the TLDN to visited location register 140 in an IS-41 message 180e. Visited location register 150 then sends via STP 135 to home location register 130 an IS-41 RouteRequest response message 180f, which includes the TLDN. When
- 20 home location register 130 receives the IS-41 RouteRequest response message 180f via STP 135, home location register 130 sends via STP 235 to server node 210 an IS-41 LocationRequest response message 230c, which includes the TLDN.

- 25 Since the TLDN in the IS-41 LocationRequest response message 230c does not match the mobile identification number associated with wireless modem 175₁, connection module 380 determines that wireless modem 175₁ resides outside of its home area. Using the TLDN, connection module 380 then establishes a call 230d to wireless modem 175₁ via a route that includes wireline switch 110, PSTN network 160, and visited wireless switch 150 (step 690).

For example, connection module 380 seizes via peripheral module 340 a modem from the bank of modems interfacing wireline switch 110, and using the TLDN associated with wireless modem 175₁, initiates call 230d to wireless modem 175₁. Connection module 380 may initiate and establish call 230d using a dialup protocol, such as the Point-To-Point protocol. For
5 example, connection module may invoke the Microsoft Dialer software to establish call 230d to wireless modem 175₁.

When connection module initiates call 230d, wireless modem 175₁ receives a ring signal from visited wireless switch 150. Wireless modem 175₁ then notifies a dialup program running on mobile terminal 178₁, such as the Microsoft Dialer software, and waits for a response. When
10 the dialup program responds, wireless modem 175₁ sends an answer signal via visited wireless switch 150 to server node 210, thus establishing call 230d between mobile terminal 178₁ and wireline terminal 155.

When call 230d is established to mobile terminal 178₁, connection module 380 sends the data portion 722 of each of the data packets 230a via call 230d to mobile terminal 178₁.
15 Accordingly, only a single call 230d or connection is established in telecommunications network 200 to provide data communication between wireline terminal 155 and mobile terminal 178₁ when mobile terminal 178₁ resides outside of its home area.

In another embodiment, server node 210 is preassigned K unique IP addresses and is configured to associate the IP address information in data packets received from wireline
20 terminal 155 to mobile terminals 178₁-178_K. Accordingly, to establish communication with mobile terminals 178₁-178_K, wireline terminal 155 segments data into one or more data packets each of which includes as its destination address one of the K IP addresses assigned to server node 210. Wireline terminal 155 then transmits the data packets via packet network 220 to server node 210. When server node 210 receives each data packet, server node 210 associates
25 the IP destination address information in the data packet with one of mobile terminals 178₁-178_K and establishes a connection to the associated mobile terminal.

Figure 8 is a block diagram of mobile identification table 384 in server node 210, in

accordance with methods and systems consistent with the invention, where server node 210 is assigned K IP addresses. As shown, mobile identification table 384 includes entries 800_1-800_N , where N is an integer. Each entry includes an IP address 810 and a mobile identification number 820. Each mobile identification number 820 identifies one of wireless modems 175_1-
5 175_K .

Figure 9 illustrates a packet format for communication between wireline terminal 155 and server node 210, in accordance with methods and systems consistent with the invention, where server node 210 is assigned K IP addresses. In the embodiment shown, data packet 230a may be in the form of an IP packet, which includes a header field 910 and a payload field 920. The
10 destination address field in header field 910 may include one of K IP addresses assigned to server node 210. Payload field 720 includes a data portion 922, which may include information in any format such as, text, video, and audio.

In this embodiment, connection mode 380 performs the steps 600 through 660 shown in Figure 6 and described above, with the following modifications: Wireline terminal 155 segments
15 data into one or more IP packets 230a, which are addressed to one of K IP addresses assigned to server node 210. To establish communication with one of mobile terminals 178_1-178_K , for example mobile terminal 178_1 , wireline terminal 155 sends the data packets 230a to server node 210. When server node 210 receives the data packets 230a, connection module 380 determines a mobile identification number associated with wireless modem 175_1 based on the IP
20 address in the destination address field in header 910 of each of the data packets 230a. For example, using the destination IP address as an index into mobile identification table 384, connection module 380 determines the associated mobile identification number. Connection module 380 then determines a home location register associated with the determined mobile identification number, for example home location register 130, and establishes a connection to
25 mobile terminal 178_1 by performing the steps described above.

Although aspects of one implementation are depicted as being stored in memory, one skilled in the art will appreciate that all or part of systems and methods consistent with the

present invention may be stored on or read from other computer-readable media, such as secondary storage devices, like hard disks, floppy disks, and CD-ROM; a carrier wave received from a network such as the Internet; or other forms of ROM or RAM. Finally, although specific components of a wireline switch and signaling node have been described, one skilled in the art will appreciate that a wireline switch and signaling node suitable for use with methods and systems consistent with the present invention may contain additional or different components.

While it has been illustrated and described what are at present considered to be preferred embodiments and methods of the present invention, it will be understood by those skilled in the art that various changes and modifications may be made, and equivalents may be substituted for elements thereof without departing from the true scope of the invention.

In addition, many modifications may be made to adapt a particular element, technique or implementation to the teachings of the present invention without departing from the central scope of the invention. Therefore, it is intended that this invention not be limited to the particular embodiments and methods disclosed herein, but that the invention include all embodiments falling within the scope of the appended claims.

WHAT IS CLAIMED IS:

1. A method for communicating data from a wireline terminal to a mobile terminal in a telecommunications network, said method comprising the steps of:
receiving by a server data destined for the mobile terminal;
identifying a mobile identification number associated with the mobile terminal;
5 determining a route that excludes a home node associated with the identified mobile identification number when a visited node serves the identified mobile identification number; and
sending the received data to the mobile terminal on a connection initiated by the server and established via the determined route.
2. The method of claim 1, further comprising the steps of:
receiving by the server data from the mobile terminal on the established connection; and
sending to the wireline terminal the data received from the mobile terminal.
3. The method of claim 1, further comprising the step of:
determining by the server another route that includes the home node when the home node serves the identified mobile identification number.
4. The method of claim 1, further comprising the step of:
sending the data by the wireline terminal to the server to establish communication with the mobile terminal.
5. The method of claim 1, further comprising the step of:
sending the data by the wireline terminal to the server via a packet network to establish communication with the mobile terminal.

6. The method of claim 1, wherein the identifying step comprises the step of:
identifying the mobile identification number based on an identifier associated with the mobile terminal.
7. The method of claim 1, wherein the identifying step comprises the step of:
identifying the mobile identification number based on an Internet Protocol (IP) address associated with the server and the mobile terminal.
8. The method of claim 1, wherein the determining step comprises the step of:
identifying a home location register based on the identified mobile identification number.
9. The method of claim 1, wherein the determining step comprises the step of:
requesting the route from a home location register serving the identified mobile identification number.
10. The method of claim 1, wherein the determining step comprises the step of:
receiving from a home location register serving the identified mobile identification number a temporary local directory number for establishing the connection to the mobile terminal.
11. The method of claim 1, wherein the sending step comprises the step of:
establishing the connection to the mobile terminal via a modem that interfaces the server and a wireline switch.
12. The method of claim 1, wherein the sending step comprises the step of:
establishing the connection to the mobile terminal via a modem that interfaces the

server and a wireless switch.

13. The method of claim 1, wherein the sending step comprises the step of:
initiating a call by the server to the mobile terminal based on a temporary location
directory number received from a home location register associated with the mobile terminal.

14. The method of claim 1, wherein the sending step comprises the step of:
initiating a call by the server to the mobile terminal based on a temporary location
directory number received from the visited node serving the identified mobile identification
number.

15. A method for communicating data from a wireline terminal to a mobile terminal
in a telecommunications network, said method comprising the steps of:
assembling by the wireline terminal data into one or more data packets; and
sending the data packets to a server for communicating the data packets to the
5 mobile terminal on a connection initiated by the server such that the connection is established via
a route that excludes a home node associated with the mobile terminal when the mobile terminal
resides outside of a geographical area served by the home node.

16. The method of claim 15, wherein the assembling step comprises the step of:
including in the data packets an identifier associated with the mobile terminal.

17. The method of claim 15, wherein the assembling step comprises the step of:
including in the data packets an Internet Protocol (IP) address associated with the
server and the mobile terminal.

18. The method of claim 15, further comprising the steps of:

preassigning a plurality of Internet Protocol (IP) addresses to the server; and
configuring the server to associate one of the preassigned IP addresses with the
mobile terminal.

19. An apparatus for communicating data between a wireline terminal and a mobile
terminal in a telecommunications network, said system comprising:

a memory including

- 5 a first table including information for identifying a mobile identification
number associated with the mobile terminal; and
code for receiving from the wireline terminal one or more data packets
destined for the mobile terminal, and for determining a route that excludes a home node
associated with the mobile identification number when a visited node serves the mobile
identification number, and for establishing via the determined route a connection to the mobile
10 terminal, and for sending the data packets on the established connection to the mobile
terminal; and
a processor for running the code.

20. The apparatus of claim 19, wherein the information in the first table includes the
mobile identification number and an identifier associated with the mobile terminal.

21. The system of claim 19, wherein the information in the first table includes the
mobile identification number and an Internet Protocol (IP) address associated with the mobile
terminal and the apparatus.

22. The system of claim 19, wherein the memory further includes:
a second table including information for identifying a home location register
associated with the mobile identification number.

23. The system of claim 22, wherein the information in the second table includes a point code associated with the home location register.

24. The system of claim 22, wherein the information in the second table includes a range of one or more directory numbers associated with the home location register.

25. A system for communicating data between a wireline terminal and a mobile terminal in a telecommunications network, said system comprising:

a server comprising

5 a first table including information for identifying a mobile identification number associated with the mobile terminal;

a second table including information for identifying a home location register associated with the mobile identification number; and

10 code for receiving from the wireline terminal one or more data packets destined for the mobile terminal, and for determining a route that excludes a home node associated with the mobile identification number when a visited node serves the mobile identification number, and for establishing via the determined route a connection to the mobile terminal, and for sending the data packets on the established connection to the mobile terminal;

a processor for running the code; and

15 a packet network for providing communication between the wireline terminal and the server.

26. The system of claim 25, further comprising:

a plurality of modems interfacing the server and a wireline switch for establishing communication between the server and the mobile terminal.

27. The system of claim 25, further comprising:

one or more modems interfacing the server and a wireless switch for establishing

communication between the server and the mobile terminal.

28. A network, comprising:

a home node serving a mobile terminal when the mobile terminal is in a geographical area served by the home node;

5 a visited node serving the mobile terminal when the mobile terminal is outside of the geographical area served by the home node; and

10 a server for receiving from a wireline terminal one or more data packets destined for the mobile terminal, and for determining a route that excludes the home node when the mobile terminal is served by the visited node, and for establishing via the determined route a connection to the mobile terminal, and for sending the data packets on the established connection to the mobile terminal.

29. A computer-readable medium capable of configuring a computer to perform a method for communicating data between a wireline terminal and a mobile terminal in a telecommunications network, said method comprising the steps of:

5 receiving from the wireline terminal data destined for the mobile terminal;
identifying a mobile identification number associated with the mobile terminal;
determining a route that excludes a home node associated with the identified mobile identification number when a visited node serves the identified mobile identification number;

10 establishing a connection via the determined route to the mobile terminal; and
sending the data to the mobile terminal on the established connection.

30. A method for communicating data from a wireline terminal to a mobile terminal in a telecommunications network, said method comprising the steps, performed by a server, of:

receiving data destined for the mobile terminal; and

PATENT
GTE DOCKET NO. 99-003

[illegible]




FIGURE 1




FIGURE 3

Figure 1 is a schematic diagram of the experimental setup. It shows a subject seated at a table, looking at a screen. On the screen, there is a starting point (a small circle) and a target (a small square). The distance between the starting point and the target is labeled '400'. The distance from the subject's eye to the screen is labeled '400 N'. A dashed line indicates the path of the hand from the starting point to the target.

MOBILE TERMINAL ID	MOBILE IDENTIFICATION NUMBER (MIN)
--------------------------	---------------------------------------




FIGURE 5


```

graph TD
    600[Receive A Data Packet From A Wireline Terminal] --> 610{Connection To Mobile Terminal Exists?}
    610 -- Yes --> 620[Send Data Portion To Mobile Terminal On Existing Connection]
    610 -- No --> 630[Determine Mobile Identification Number Associated With Mobile Terminal]
    630 --> 640[Identify An HLR Associated With Mobile Terminal]
    640 --> 650[Send A Location Request To Identified HLR]
    650 --> 660[Receive From Identified HLR A Response To Location Request]
    660 --> 670{Location Request Response Includes A TLDN?}
    670 -- No --> 680[Establish Connection To Mobile Terminal Using Determined Mobile Identification Number]
    670 -- Yes --> 690[Establish Connection To Mobile Terminal Using TLDN]
  
```

FIGURE 6

$P_{11}, P_{12}, \dots, P_{1n}$
 $P_{21}, P_{22}, \dots, P_{2n}$
 \vdots
 $P_{m1}, P_{m2}, \dots, P_{mn}$

230
a




FIGURE 7

The diagram shows a rectangular domain divided into several horizontal layers. The top layer is labeled 800_I and the bottom layer is labeled 800_N . Three small squares are arranged vertically in the center of the domain. A dashed line extends from the bottom-left corner.

FIGURE 8

FIG. 9 is a schematic diagram of a data structure 230a. The data structure 230a is shown as a rectangular block divided into two main sections. The upper section is labeled 920 and contains the word "PAYLOAD". The lower section is labeled 922 and contains the word "DATA". A dashed line separates the two sections. The entire structure is labeled 230a at the top left. The label 910 is positioned to the right of the structure, pointing towards the "PAYLOAD" section. The label "HEADER" is positioned below the "PAYLOAD" section, pointing to a small rectangular area within the "PAYLOAD" section.




FIGURE 9

DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

Attorney Docket No. 99-003

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

METHOD AND SYSTEM FOR COMMUNICATING DATA FROM WIRELINE TERMINALS TO MOBILE TERMINALS

the specification of which (check one) ☒ is attached hereto. ☐ was filed on _____ as Appln. Serial No. _____ and was amended on _____ (if applicable). I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, Section 1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)			<u>Priority Claimed</u>
_____	_____	_____	<input type="checkbox"/> Yes <input type="checkbox"/> No
(Number)	(Country)	(Day/Month/Year filed)	

I hereby claim the benefit under Title 35, United States Code, 119(e) of any United States provisional application(s) listed below.

_____	_____
(Application Number)	(Filing Date)

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) listed below and insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, Section 1.56 which occurred between the filing date of the prior application and the national or PCT international filing date for this application:

_____	_____	_____
(Appln. Serial No.)	(Filing Date)	(Status--patented, pending, abandoned)

Attorney Docket No. 99-003

I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

Leonard C. Suchyta, Reg. No. 25,707, Floyd E. Anderson, Reg. No. 33,825 and W. Eric Webostad, Reg. No. 35,406

Address all telephone calls to W. Eric Webostad at telephone no. (781) 466-4013

Address all correspondence to Leonard C. Suchyta
GTE Service Corporation
600 Hidden Ridge, HQE03G13
Irving, TX 75038

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

FULL NAME OF SOLE OR FIRST INVENTOR Walter Wesley Howe

Inventor's signature Walter Wesley Howe Date Feb. 28, 2000

Residence Alpharetta, Georgia Citizenship USA

Post Office Address 6701 Webb Bridge Ct., Alpharetta, GA 30004